

OHS, "OVERHEIGHT STOP", 39.5 x 15.5 or 48 x 18

MATERIALS

Extruded Aluminum 1.5" Sq.
Reinforced ¼" Aluminum Plate Corners
Face Material - ¼" Impact resistant Dark Black tinted polycarbonate.
Back Material - ¼" High density black polyethylene (HDPE).

ELECTRICAL

3 inch OVERHEIGHT single row (5x7)
5 inch STOP single row (7x11)
12 VDC @ 3.5 Amps, approx. 42 Watts.

5 inch OVERHEIGHT STOP single row (7x11)
12 VDC @ 4.1 Amps, approx. 49 Watts.
Operating Temp. -40 to +90 deg.C (-40 to +194 deg.F).
Optional 120VAC input Remote 60 Watt UL power supply provided.

LED's

RED 5mm Cree Hi-brightness 30 degree.
Message blanks out when turned off.

FINISH

Standard Black Powdercoat or Natural Aluminum Clear Coat.
Custom colors available on request.

PHYSICAL

Standard sign Sealed. IP65 weather tight.
Viewable 36w x 12h x 1.75d (Actual 39.5w x 15.5h x 1.75d)
Rear T-Slot Spacing (Center to Center T-Slot Top to Bottom 14"h)
Extra wide sign. IP65 weather tight.
Viewable 44.5w x 15.5h x 1.75d (Actual 48w x 18h x 1.75d)
Mounting - (4) movable S.S. 5/16-18 T-Slot Nuts in top(2) and bottom(2) slots
Mounting Weight - 22lbs (36x12), 30 lbs (48x18)



39.5 x 15.5



48 x 18

©2015-2016

Available from

NOVA TECH, LLC

184 Goose Lane, Tolland, CT 06084

860-871-4180