

**R3-1 & R3-2 , No Right Turn & No Left Turn symbols****MATERIALS**

Extruded Aluminum 1.5" Sq.  
 Reinforced ¼" Aluminum Plate Corners  
 Face Material - ¼" Impact resistant clear pebble texture UV stable polycarbonate.  
 Back Material - ¼" High density black polyethylene (HDPE) or ABS.  
 Stainless Steel Fasteners.

**ELECTRICAL**

24" sign, 12 VDC @ 1.2Amp. (Approx 15 watts).  
 30" sign, 12 VDC @ 3.9 A. (Approx 46 watts).  
 Remote mounted 12 VDC UL power supply included.  
 Standard Watertight Junction box provided

**LED's**

RED + WHITE 5mm Hi-brightness.  
 Message blanks out when turned off.

**FRAME FINISH**


Standard Black Powdercoat or Natural Aluminum Clear Coat.  
 Custom colors available on request.

**PHYSICAL**

R3-1 - NO RIGHT TURN Symbol, 24" x 24" or 30" x 30"  
 R3-2 - NO LEFT TURN SYMBOL , 24" x 24" or 30" x 30"  
 Sealed sign, No user serviceable parts.  
 Actual Size (27.5" square or 33.5" square x 1.75" deep)  
 Mounting - (4) movable S.S. 5/16-18 T-Slot Nuts (2) in top and (2) in bottom slot  
 on rear of sign.  
 T-Slot Spacing CTC 26" (24"sign), CTC 32" (30"sign).  
 T-Slot Length 18" (24"sign), 24" (30"sign).  
 Weight - 26lbs (24") and 32lbs (30").



Black Frame



Natural Frame

Available from

**NOVA TECH, LLC**

184 Goose Lane, Tolland, CT 06084

860-871-4180

## Power & Connection Options

**Standard** - NEMA watertight housing with knockouts and screw terminal block . IP66 rated. (RED = + 12 vdc, BLK = dc common).

Location : Back, lower corner.



**Optional** - Watertight cable grip and 10 ft of color coded 18 AWG Lead-In cable. (RED = + 12 vdc, BLK = dc common).

Location : Back, lower corner.



**Optional** - Power Supply mounted in NEMA watertight housing.

Housing mounted to right side T-Slot track on rear of sign. Pre-wired 10ft Lead-in to Power supply DC Output. Watertight cable grip on housing for AC cable input.



©2004-2016