

“ ENTERING TRAFFIC “

MATERIALS

Extruded Aluminum 1.5” Sq.
Reinforced ¼” Aluminum Plate Corners
Face Material - ¼” Impact resistant clear dark tint polycarbonate
Back Material - ¼” AlumaLite or HDPE

FINISH

Standard Black Powdercoat or Natural Aluminum Clear Coat.
Stainless Steel 304 Hardware.

LED's

Text :
Single row LED characters (5 x 7 matrix).
5mm Amber Hi-brightness CREE LED's (591nm).
Viewing Angle 15 degree.
Border : (Optional)
Single Row 3528 Amber LED Strip (180 deg).

ELECTRICAL

Text : 12 VDC @ 3.3 Amps, approx. 39 Watts.
Border : 12 VDC, approx. 12 Watts.
Operating Temp. -40 to +90 deg.C (-40 to +194 deg.F).
12 VDC @ 60 Watt UL power supply included (IP67).
NEMA 4, IP66 Junction Box on rear.

PHYSICAL

Standard sign Sealed. IP65 weather tight.
Viewable 36w x 36h x 1.75d (Actual 39.5w x 39.5h x 1.75d)
(Junction box depth 2.24” off rear of sign)
Mounting - (8) movable S.S. 5/16-18 T-Slot nuts, 2 per side.
Sign Weight - approx 40 lbs (36x36).
1 year Limited Warranty.

M-Systems Inc. ©2018

Available from

NOVA TECH, LLC



